



Aeroquip
GH681-32
Hose - SCHLAUCH

* Representative Image

Product Specifications

Abrasion Resistance	Premium
Application	Compact construction equipment, Agricultural equipment, Arial lift equipment, and Other industrial applications needing 1SC pressures
Burst Pressure	2400 psi
Certification(s)	EN853 1SN SAE 100R17 SAE 100R1AT ABS EN853 1ST EN857 1SC
Color	Black
Compliances	DNV USCG MSHA Approved
Conductivity	Conductive
Construction	1 Ply Braid
Cover Material	Synthetic Rubber
Dash Size	-32
Description Product Name	Eaton Aeroquip GH681 Series Rubber Hydraulic Braided Hose
Description Short	Hose
ECCN	EAR99
Impulse Cycle Life	400000 cycle
Inside Diameter	2 inch
Lay Line Style	Ink Transfer
Maximum Working Temperature	258.8 degree Fahrenheit
Minimum Bend Radius	12.4 inch
Minimum Working Temperature	-50.8 degree Fahrenheit
Outside Diameter	2.58 inch
Product Height	2.58
Product Height UOM	inch
Product Length	1
Product Length UOM	foot
Product Trade Name	GH681 Series
Product Weight	1.29
Product Weight UOM	pound
Product Width	2.58
Product Width UOM	inch

Qualified Hose Fittings	TTC
Reinforcement Material	Wire
Sub Brand	Aeroquip
Tube Material	Synthetic Rubber
Working Pressure	600 psi