

Check Valves



Check Valves

C* G-800 Series

***Note**

The valve seat is installed through the front as shown on the C3G, C4G & C5G series. On the C2G series, the seat is installed from the back of the mounting surface.

If body is required, order a new valve.

**CAUTION**

When a C5G is used to replace a C2G or C3G, drill an appropriate hole in the mounting surface to accommodate the extra rest pin of the C5G and plug the unused hole. The pins prevent reversal of the valve on the mounting surface, which could cause a system malfunction and/or injury to personnel.

154132 "O" Ring
81976 Plug

Seal (See table)

Pin (See table)

154128 "O" Ring

315932 Plug


Model	Spring	Cracking Pressure	Valve	Plug	*Seat	Seals (2 req'd)	Pin (2 req'd)
C2G-815	2943	5 PSI	81589	—	104403	262395	102679
C3G/C4G-815					263886	154020	160571
C5G-815							
C2G-815-S2	36316	35 PSI			104403	262395	102679
C3G/C4G-815-S2					263886	154020	160571
C5G-815-S2							
C2G-815-S3	25896	50 PSI			104403	262395	102679
C3G/C4G-815-S3					263886	154020	160571
C5G-815-S3							
C2G-815-S8	32999	75 PSI			104403	262395	102679
C3G/C4G-815-S8					263886	154020	160571
C5G-815-S8							
C2G-815-S12	2943	5 PSI	108708	81592	104403	262395	102679
C3G/C4G-815-S12					263886	154020	160571
C5G-815-S12							
C2G-815-S17	84235	125 PSI	81589	—	104403	262395	102679
C3G/C4G-815-S17					263886	154020	160571
C5G-815-S17							
C2G-815-S19	2287	20 PSI			104403	262395	102679
C3G/C4G-815-S19					263886	154020	160571
C5G-815-S19							
C2G-815-S20	83902	1 PSI			104403	262395	102679
C3G/C4G-815-S20					263886	154020	160571
C5G-815-S20							

Order and use mounting bolt kit BK CG825-615 if a C4G/C5G-825 valve is used to replace a C2G-825 or a C3G-825 valve.

If body is required, order a new valve.



CAUTION
When a C5G is used to replace a C2G or C3G, drill an appropriate hole in the mounting surface to accommodate the extra rest pin of the C5G and plug the unused hole. The pins prevent reversal of the valve on the mounting surface, which could cause a system malfunction and/or injury to personnel.



Model	Spring	Cracking Pressure	Valve
C2G-825	2284	5 PSI	108359
C3G/C4G-825			
C5G-825			
C2G-825-S2	2953	35 PSI	
C3G/C4G-825-S2			
C5G-825-S2			
C2G-825-S3	29059	50 PSI	
C3G/C4G-825-S3			
C5G-825-S3			
C2G-825-S8	39778	75 PSI	
C3G/C4G-825-S8			
C5G-825-S8			
C2G-825-S12	2284	5 PSI	182004
C3G/C4G-825-S12			
C5G-825-S12			
C2G-825-S17	64062	125 PSI	108359
C3G/C4G-825-S17			
C5G-825-S17			
C2G-825-S19	106669	20 PSI	
C3G/C4G-825-S19			
C5G-825-S19			
C2G-825-S20	2950	1 PSI	
C3G/C4G-825-S20			
C5G-825-S20			
C5G-825-S44	64062	125 PSI	

Model	Seals		Pin (2 req'd)
	Inlet	Outlet	
C2G	42310		102679
C3G	▲154026	▲154077	160571
C4G			
C5G			

Plug	O Ring	Model
14137	▲154077	C2G/C3G/C4G
347831	▲161467	C5G
Torque plug to 40-50 lb.ft. (54-68 N.m)		

C3G/C4G/C5G-825 ▲ Seal Kits	
Standard	919381
F3	919382

For satisfactory service life of these components, use full flow filtration to provide fluid which meets ISO cleanliness code 16/13 or cleaner. Selections from pressure, return, and in-line filter series are recommended.

Products we offer:

- Cartridge valves
- DCV directional control valves
- Electric converters
- Electric machines
- Electric motors
- Gear motors
- Gear pumps
- Hydraulic integrated circuits (HICs)
- Hydrostatic motors
- Hydrostatic pumps
- Orbital motors
- PLUS+1® controllers
- PLUS+1® displays
- PLUS+1® joysticks and pedals
- PLUS+1® operator interfaces
- PLUS+1® sensors
- PLUS+1® software
- PLUS+1® software services, support and training
- Position controls and sensors
- PVG proportional valves
- Steering components and systems
- Telematics

Hydro-Gear

www.hydro-gear.com

Daikin-Sauer-Danfoss

www.daikin-sauer-danfoss.com

Danfoss Power Solutions is a global manufacturer and supplier of high-quality hydraulic and electric components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market as well as the marine sector. Building on our extensive applications expertise, we work closely with you to ensure exceptional performance for a broad range of applications. We help you and other customers around the world speed up system development, reduce costs and bring vehicles and vessels to market faster.

Danfoss Power Solutions – your strongest partner in mobile hydraulics and mobile electrification.

Go to www.danfoss.com for further product information.

We offer you expert worldwide support for ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide you with comprehensive global service for all of our components.

Local address:

**Danfoss
Power Solutions (US) Company**
2800 East 13th Street
Ames, IA 50010, USA
Phone: +1 515 239 6000

**Danfoss
Power Solutions GmbH & Co. OHG**
Krokamp 35
D-24539 Neumünster, Germany
Phone: +49 4321 871 0

**Danfoss
Power Solutions ApS**
Nordborgvej 81
DK-6430 Nordborg, Denmark
Phone: +45 7488 2222

**Danfoss
Power Solutions Trading
(Shanghai) Co., Ltd.**
Building #22, No. 1000 Jin Hai Rd
Jin Qiao, Pudong New District
Shanghai, China 201206
Phone: +86 21 2080 6201

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.