



Directional Valves with Direct Current Solenoids

THIS PART

IS
REPLACED
BY

THESE PARTS

Solenoid S/A
(See table)

11011 Screw
(4 req'd)

281545 Gasket


The same change applies to this end for models with two solenoids

Voltage DC	Solenoid S/A	Coil	F3 S/A Solenoid	F3 Coil
6	290838	291582	—	—
12	290839	291583	751283	751284
24	290840	291584	393091	393090
28	320223	320224	—	—
30	320227	320228	—	—
32	323224	323225	—	—
36	326039	326311	—	—
40	392502	392503	—	—
48	324739	324740	585214	585215
50	385683	385684	—	—
60	320641	320642	—	—
72	326043	326315	—	—
90	326038	326310	—	—
110	320218	320219	750463	750464
115	321986	321987	—	—
120	326041	326313	—	—
125	318717	318718	751264	751265
130	326042	326314	—	—
220	326040	326312	751270	751276
230	318392	318393	751266	751267
240	326044	326316	751268	751269
250	306083	306084	751272	751273

On Model	Shown on Drawing			To Make Model
	-50	-51	-53/54	
DF5S4-16*A-50/53	I-3486-S	I-3622-S	I-3622-S	DF5S4-16*A-*DC-50/53
DF5S4-16*B-53	_____			DF5S4-16*B-*DC-53
DF5S4-16*C-50/53	I-3482-S			DF5S4-16*C-*DC-50/53
DF5S4-16*N-50/51/53				I-3482-S
DF5S4-06*A-50/51	I-3492-S	I-3502-S	I-3624-S	DG5S4-16*A-*DC-50/51
DF5S4-06*C-50/51	I-3490-S	I-3473-S		DG5S4-06*C-*DC-50/51
DF5S4-06*D-50/51	I-3493-S	I-3504-S		DG5S4-06*D-*DC-50/51
DF5S4-06*N-50/51	I-3491-S	I-3474-S		DG5S4-06*N-*DC-50/51
DF5S4-10*A-50/51/53/54	I-3496-S	I-3513-S	I-3624-S	DG5S4-10*A-*DC-50/51/53/54
DF5S4-10*B-53/54	_____	_____		DG5S4-10*B-*DC-53/54
DF5S4-10*C-50/51/53/54	I-3494-S	I-3509-S		DG5S4-10*C-*DC-50/51/53/54
DF5S4-10*D-50/51/53/54	I-3497-S	I-3514-S	I-3625-S	DG5S4-10*D-*DC-50/51/53/54
DF5S4-10*N-50/51/53/54	I-3495-S	I-3512-S	I-3624-S	DG5S4-10*N-*DC-50/51/53/54

Model Code

D * 5 S 4 (L) - * * * * (X) (*) - (*) - (E) - (T) - (*) - * DC - 5*



1 Model Series

D - Directional valve

2 Mounting

F - Flange connection

G - Subplate or manifold mounted

3 Operation

Solenoid controlled, pilot operated

4 Sliding Spool

5 Flow Directions

4 - 4 way

6 Indicator lights

L - Solenoid

Omitted - None

7 Series

06 - Series 60

10 - Series 100

16 - Series 160

8 Type of Main Stage Spool

9 Spring

A - Spring offset

C - Spring centered

D - Pressure centered

N - No-spring detented

10 Pressure

"X" - Fast response models
(for 100 series pressure centered
models, "X" is available in the "A"
pilot pressure range only)

Omitted - Low shock model

11 Pilot Pressure Range (100 series pressure)

A - 300 to 1000 PSI

B - 1000 to 2000 PSI

12 Spool Control Modifications (Omit if not required)

1 - Stroke adjustments

2 - Pilot choke

3 - Pilot choke and stroke adjustment

7 - Stroke adjustment "A" end only

8 - Stroke adjustment "B" end only

13 Pilot Pressures

E - External pilot pressure

Omitted - Internal pilot pressure

14 Pilot Drain

T - Internal pilot drain
(not available on open center spools
unless external pilot pressure (E)
is used)

Omitted - External pilot drain

15 Check Valve

K - 5 PSI cracking pressure

L - 30 PSI cracking pressure

R - 50 PSI cracking pressure

S - 75 PSI cracking pressure

16 DC Solenoid

17 Solenoid Voltage

18 Design

-50/-51/-53/-54

Products we offer:

- Cartridge valves
- DCV directional control valves
- Electric converters
- Electric machines
- Electric motors
- Gear motors
- Gear pumps
- Hydraulic integrated circuits (HICs)
- Hydrostatic motors
- Hydrostatic pumps
- Orbital motors
- PLUS+1® controllers
- PLUS+1® displays
- PLUS+1® joysticks and pedals
- PLUS+1® operator interfaces
- PLUS+1® sensors
- PLUS+1® software
- PLUS+1® software services, support and training
- Position controls and sensors
- PVG proportional valves
- Steering components and systems
- Telematics

Hydro-Gear

www.hydro-gear.com

Daikin-Sauer-Danfoss

www.daikin-sauer-danfoss.com

Danfoss Power Solutions is a global manufacturer and supplier of high-quality hydraulic and electric components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market as well as the marine sector. Building on our extensive applications expertise, we work closely with you to ensure exceptional performance for a broad range of applications. We help you and other customers around the world speed up system development, reduce costs and bring vehicles and vessels to market faster.

Danfoss Power Solutions – your strongest partner in mobile hydraulics and mobile electrification.

Go to www.danfoss.com for further product information.

We offer you expert worldwide support for ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide you with comprehensive global service for all of our components.

Local address:

**Danfoss
Power Solutions (US) Company**
2800 East 13th Street
Ames, IA 50010, USA
Phone: +1 515 239 6000

**Danfoss
Power Solutions GmbH & Co. OHG**
Krokamp 35
D-24539 Neumünster, Germany
Phone: +49 4321 871 0

**Danfoss
Power Solutions ApS**
Nordborgvej 81
DK-6430 Nordborg, Denmark
Phone: +45 7488 2222

**Danfoss
Power Solutions Trading
(Shanghai) Co., Ltd.**
Building #22, No. 1000 Jin Hai Rd
Jin Qiao, Pudong New District
Shanghai, China 201206
Phone: +86 21 2080 6201

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.