


Pressure Relief

Balanced Piston High Flow Relief & Sequence Valve

CS-H06-*-V(Y)-50

Model	¹ Spring	Pressure Range PSI	¹ Included in Cover S/A
C*-H06-BV-50	2280	125-1000	941280
C*-H06-BVY-50			941283
C*-H06-CV-50	583937	500-2000	941281
C*-H06-CVY-50			941284
C*-H06-FV-50	2281	1500-3000	941282
C*-H06-FVY-50			941285



Model	² Body
CS-H06-*-V-50	581701

⁴Available in Lot Kits of 25 pieces


1485	944064
36212	944053
64520	944068
326317	944073
343740	944038
315932	944062

²Not available for sale as individual parts

³Included in F3 Seal Kit 919922

Model Code Breakdown

(F3) C * - H06 - * - V (Y) - 50



1 Seals

F3 - Multi-fluid capability (Viton® seals)

Viton is a registered trademark of E.I. DuPont

2 Model Series

C - Relief valve

3 Thread Type

S - SAE straight

4 Size

H06 - 3/4 inch high flow

5 Pressure Range

B - 125-1000

C - 500-2000

F - 1500-3000

6 Vent Pressure

V - High vent pressure

7 External Drain Feature

Y - Sequence valve
(Omit for standard relief.)

8 Design

For satisfactory service life of these components, use full flow filtration to provide fluid which meets ISO cleanliness code 18/15 or cleaner..