


Vane Type Single Pump

(F3)-V10(*) Series -10 & 20 Designs

SAE rated capacity (V10/F/P cartridgekits)

USgpm	○Rotor	○Vane Kit	○Ring	Pin (V10)	Pin (V10F/V10P)	Bolt (V10)	Bolt (V10F)	Bolt (V10P)	○Cart. Kit
1	317681	923499	317674	2460	231042	11156	432509	295344	923471
2			317675						923470
3			317676						923496
4	351247	923500	317677	39640	2456	1278	295344	432511	923469
5			317678						923468
6	357286	923501	355641	16662	351963		432511	295346	923497
7			331813						923498



Cover port connections


Code	V10 cover	V10F cover	V10P cover
P	372863	379543	—
R	372864	—	—
S	372865	—	—
Y	377829	—	—
T	—	372851	—
K	—	—	388262

Pressure setting–V10P/V10F (Omit for V10)


Code	Pressure settingV10P/V10F	♦ V10P Spring	■ V10F controlS/A
A	250 PSI	252886	229613
B	500 PSI	2280	233018
C	750 PSI		232794
D	1000 PSI	2282	232795
E	1250 PSI		232796
F	1500 PSI		232797
G	1750 PSI	2281	232798
H	2000 PSI		232799
J	2250 PSI		233019
K	2500 PSI		233020

- Included in V10 cartridge kit.
- ▲ Included in seal kit 923548
F3 equivalent seal kit 919772

Model	Body
V10-***-20	574164
V10-***-20	352699
V10-***-20	317668
V10-***-10	370468




Model	Shaft	Key	Nut	Shaft type
V10-****-1	374338	142843		Straight
V10-****-3	374340	1605	8948	Theaded
V10-****-4	378959	1606	8948	Theaded
V10-****-6	382250	1609		Straight
V10-****-11	374339			Splined
V10-****-12	375480			Splined
V10-****-27	380281			Tang
V10-****-34	375485			Theaded
V10-****-38	387481			Splined



Typical Cutaway View

Model Code



1 Special seals

F3 – Special “O”Rings & seals for mineral oil & fire resistant fluid

2 Vane Pump

3 Series 10

4 Pump cover options

F – Flow control cover
P – Priority valve cover
Omitted –Standard cover

5 Mounting

1 –2 Bolt flange (SAE “A” size)
2 –Foot bracket at 12 O’ Clock (Viewed from shaft end)
23 –Foot bracket at 3 O’ Clock
26 –Foot bracket at 6 O’ Clock
29 –Foot bracket at 9 O’ Clock

6 Inlet port connections

F –1.156 DIS. port
H –1 ” O.D. tube connection
K –1 ⁵/₁₆–12 UN 2B thread
P –1 ” NPT thread
S –1 ⁵/₁₆–12 straight thread
T –1 ³/₁₆–12 straight thread

7 SAE rated ring capacity USGPM (1200 RPM –100 PSI)

1 – 1 USgpm
2 – 2 USgpm
3 – 3 USgpm
4 – 4 USgpm
5 – 5 USgpm
6 – 6 USgpm
7 – 7 USgpm

8 Outlet port connections

V10 standard cover

K –1 ⁵/₁₆–12 UN 2B thread
P –1 ” NPT thread
S –1 ⁵/₁₆–12 straight thread
T –1 ³/₁₆–12 straight thread

V10F Flow control cover

Pressure

P – ³/₄–16 straight thread
T – ³/₄–16 straight thread

Tank

P – ¹/₂” NPT thread
T – ³/₄–16 straight thread

V10P Priority valve cover

Primary outlet

K – ⁹/₁₆–18 straight thread

Secondary outlet

K – ³/₄–16 straight thread

Tank

K – ⁹/₁₆–18 straight thread

9 Shaft types

1 –Straight –keyed
3 –Threaded
4 –Threaded
6 –Straight stub– keyed
11 – Spline–9 tooth
12 –Spline– 13 tooth
27 –Tang
34 –Threaded
38 –Spline– 11 tooth

10 Pressure port positions (Viewed from cover end)

A –Opposite inlet
B –90% CCW from inlet
C –Inline with inlet
D –90% CCW from inlet

11 Flow rate in USGPM through orifice in cover

1 –1 USGPM (V10P)
2 –2 USGPM (V10F)

12 Pressure setting ,V10F & V10P (Omit for standard cover)

Code

A – 250 psi
B – 500 psi
C – 750 psi
D – 1000 psi
E – 1250 psi

Code

F – 1500 psi
G – 1750 psi
H –2000 psi
J –2250 psi
K – 2500 psi

13 Design & Modification

14 Special feature suffix

15 Rotation (Viewed from shaft end of pump)

L – Left hand for counterclockwise

Products we offer:

- Cartridge valves
- DCV directional control valves
- Electric converters
- Electric machines
- Electric motors
- Gear motors
- Gear pumps
- Hydraulic integrated circuits (HICs)
- Hydrostatic motors
- Hydrostatic pumps
- Orbital motors
- PLUS+1® controllers
- PLUS+1® displays
- PLUS+1® joysticks and pedals
- PLUS+1® operator interfaces
- PLUS+1® sensors
- PLUS+1® software
- PLUS+1® software services, support and training
- Position controls and sensors
- PVG proportional valves
- Steering components and systems
- Telematics

Danfoss Power Solutions is a global manufacturer and supplier of high-quality hydraulic and electric components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market as well as the marine sector. Building on our extensive applications expertise, we work closely with you to ensure exceptional performance for a broad range of applications. We help you and other customers around the world speed up system development, reduce costs and bring vehicles and vessels to market faster.

Danfoss Power Solutions – your strongest partner in mobile hydraulics and mobile electrification.

Go to www.danfoss.com for further product information.

We offer you expert worldwide support for ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide you with comprehensive global service for all of our components.

Local address:

Hydro-Gear

www.hydro-gear.com

Daikin-Sauer-Danfoss

www.daikin-sauer-danfoss.com

**Danfoss
Power Solutions (US) Company**
2800 East 13th Street
Ames, IA 50010, USA
Phone: +1 515 239 6000

**Danfoss
Power Solutions GmbH & Co. OHG**
Krokamp 35
D-24539 Neumünster, Germany
Phone: +49 4321 871 0

**Danfoss
Power Solutions ApS**
Nordborgvej 81
DK-6430 Nordborg, Denmark
Phone: +45 7488 2222

**Danfoss
Power Solutions Trading
(Shanghai) Co., Ltd.**
Building #22, No. 1000 Jin Hai Rd
Jin Qiao, Pudong New District
Shanghai, China 201206
Phone: +86 21 2080 6201