




Flow Controls, One Way Restrictor Type


FN-03; EFN-06 and EFN-10

Typical Section




Functional Symbol

All models



Model Code

F3 -(E) FN ** - ** - *



1 Special seals
For use with phosphate ester type fluids
Omit if not required

2 European product
Omit for FN-03

3 Flow control, one-way restrictor
type

4 Nominal size
03 = 3/8"
06 = 3/4"
10 = 1 1/4"

5 Design number
11 = EFN-10
20 = FN-03
21 = EFN-06

6 System connections
B = G (BSPF)
F = SAE 4-bolt flange
(EFN-06/10 only)

Basic Characteristics

Type Restrictor valve
Mounting Thread or flange
Maximum
pressure Up to 210 bar (3000 psi)
Maximum flow Up to 190 L/min
(50 USgpm)
Method of Adjustment Manual

General Description

The FN-03 and EFN-06/10 adjustable one-way restrictors are designed for applications where fluid oil flow regulation without pressure compensation is required. They can be used whenever the working load remains relatively constant.


Flow regulation is for one direction only. When the flow is reversed the valve opens against a spring and flow passes through at near zero pressure. These valves therefore cannot be used as isolating valves.

Operating Data

Maximum Pressure bar (psi)
Hydraulic petroleum oils and
common FR fluids 210 (3000)
5% – 95% oil-in-water
emulsion 140 (2000)


Flow/Pressure Data
Maximum recommended controlled flow,
L/min (USgpm), with good regulation.
FN-03 38 (10)
E FN-06 76 (20)
E FN-10 189 (50)

Minimum Controlled Flow




Pressure Drop for Free-Flow and Maximum Controlled Flow

Models FN-03 and EFN-06



Model EFN-10



Hydraulic Fluids

All models can be used with hydraulic oils, water-in-oil emulsions and water glycols. Add prefix "F3" to model designation when phosphate ester (not alkyl-based) to be used. EFN-06 and 10 models can also be used with a 5-10% concentration of soluble oil in clean water.

The extreme operating viscosity range is from 13 to 860 cSt (70 to 4000 SUS) but the recommended running range for all but soluble-oil-in-water emulsions is 13 to 54 cSt (70 to 245 SUS).

For further information about fluids see leaflet 920.

Contamination Control Requirements
Recommendations on contamination control methods and the selection of products to control fluid condition are included in Vickers by Danfoss publication 9132 or 561, "Vickers by Danfoss Guide to Systemic Contamination Control". The book also includes information on the Vickers by Danfoss concept of "ProActive Maintenance". The following recommendations are based on ISO cleanliness levels at 2 µm, 5 µm and 15 µm. For products in this catalog the recommended levels are:

Up to 210 bar (3000 psi) 19/ 17/14

Temperature Limits

Ambient

Min. -20 °C (-4 °F)
Max. +40 °C (+104 °F)

Fluid Temperature


	Petroleum oil	Water-containing
Min.	-20 °C (-4 °F)	+10 °C (+50 °F)
Max.*	+80 °C (+176 °F)	+54 °C (+130 °F)

* To obtain optimum service life from both fluid and hydraulic system 65 °C (150 °F) normally is the maximum temperature except for water-containing fluids.


For synthetic fluids consult manufacturer or Vickers by Danfoss representative where limits are outside those for petroleum use. Whatever the actual temperature range, ensure that viscosities stay within the limits specified in the "Hydraulic Fluids" section.

Installation Dimensions in mm (inches)

EFN-06 and EFN-10



FN-03



Model	A	B	C	D	E	F	G	H	J	K	L	M
EFN-06-21-F	89 (3.50)	52 (2.04)	65 (2.56)	45 (1.77)	90 (3.54)	44,5 (1.75)	22 (0.87)	47,6 (1.87)	23,9 (0.94)	22,1 (0.87)	11 (0.43)	22 (0.87)
EFN-06-21-B	89 (3.50)	52 (2.04)	65 (2.56)	45 (1.77)	90 (3.54)	44,5 (1.75)	22 (0.87)	—	—	—	—	22 (0.87)
EFN-10-11-F	116 (4.57)	73 (2.87)	80 (3.15)	58 (2.28)	100 (3.94)	47 (1.85)	25 (0.98)	58,7 (2.31)	29,4 (1.16)	30,2 (1.19)	15 (0.59)	32 (1.26)
EFN-10-11-B	116 (4.57)	73 (2.87)	80 (3.15)	58 (2.28)	100 (3.94)	47 (1.85)	25 (0.98)	—	—	—	—	32 (1.26)

Model	Thread N	SAE flange sizes Nom. bore	Pipe O.D.	Thread S
EFN-06-21-F	—	3/4"	25	3/8"-16 UNC-2B x 19 (0.75) deep
EFN-10-11-F	—	1 1/4"	38	7/16"-14 UNC x 19 (0.75) deep

Mass, kg (lb)

FN-03-20	0,6 (1.3)
EFN-06-21	1,7 (3.7)
EFN-10-11	3,7 (8.1)

Ordering Procedure

SAE 4-bolt flanges for the appropriate valves are available from Danfoss and must be ordered as, and are supplied as, separate items.

Mounting Attitude

Optional.

Products we offer:

- Cartridge valves
- DCV directional control valves
- Electric converters
- Electric machines
- Electric motors
- Gear motors
- Gear pumps
- Hydraulic integrated circuits (HICs)
- Hydrostatic motors
- Hydrostatic pumps
- Orbital motors
- PLUS+1® controllers
- PLUS+1® displays
- PLUS+1® joysticks and pedals
- PLUS+1® operator interfaces
- PLUS+1® sensors
- PLUS+1® software
- PLUS+1® software services, support and training
- Position controls and sensors
- PVG proportional valves
- Steering components and systems
- Telematics

Danfoss Power Solutions is a global manufacturer and supplier of high-quality hydraulic and electric components. We specialize in providing state-of-the-art technology and solutions that excel in the harsh operating conditions of the mobile off-highway market as well as the marine sector. Building on our extensive applications expertise, we work closely with you to ensure exceptional performance for a broad range of applications. We help you and other customers around the world speed up system development, reduce costs and bring vehicles and vessels to market faster.

Danfoss Power Solutions – your strongest partner in mobile hydraulics and mobile electrification.

Go to www.danfoss.com for further product information.

We offer you expert worldwide support for ensuring the best possible solutions for outstanding performance. And with an extensive network of Global Service Partners, we also provide you with comprehensive global service for all of our components.

Local address:

Hydro-Gear

www.hydro-gear.com

Daikin-Sauer-Danfoss

www.daikin-sauer-danfoss.com

**Danfoss
Power Solutions (US) Company**
2800 East 13th Street
Ames, IA 50010, USA
Phone: +1 515 239 6000

**Danfoss
Power Solutions GmbH & Co. OHG**
Krokamp 35
D-24539 Neumünster, Germany
Phone: +49 4321 871 0

**Danfoss
Power Solutions ApS**
Nordborgvej 81
DK-6430 Nordborg, Denmark
Phone: +45 7488 2222

**Danfoss
Power Solutions Trading
(Shanghai) Co., Ltd.**
Building #22, No. 1000 Jin Hai Rd
Jin Qiao, Pudong New District
Shanghai, China 201206
Phone: +86 21 2080 6201

Danfoss can accept no responsibility for possible errors in catalogues, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary in specifications already agreed.
All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.