

Eaton® Winner EC118 SAE 100R17



EC118

Meets/Exceeds SAE 100R17



#													
Part Number	DN	Hose I.D.		Hose O.D.		Max Operating Pressure		Burst Pressure		Minimum Bend Radius		Weight	
		mm	in	mm	in	bar	psi	bar	psi	mm	in	kg/m	lbs/ft
EC118-04L	6	6,4	0.25	12,2	0.48	210,0	3050	840,0	12200	50,8	2.00	0,18	0.12
EC118-06L	10	9,5	0.38	15,5	0.61	210,0	3050	840,0	12200	63,5	2.50	0,27	0.18
EC118-08L	12	12,7	0.50	19,0	0.75	210,0	3050	840,0	12200	88,9	3.50	0,36	0.24
EC118-10L*	16	15,9	0.62	23,8	0.94	210,0	3050	840,0	12200	101,6	4.00	0,69	0.46
EC118-12L*	19	19,0	0.75	27,7	1.09	210,0	3050	840,0	12200	120,7	4.75	0,81	0.54
EC118-16L*	25	25,4	1.00	36,0	1.42	210,0	3050	840,0	12200	152,4	6.00	1,21	0.81

* Two braids of high tensile wire

Construction

- Synthetic rubber tube
- One or two wire braid reinforcement
- Synthetic rubber cover
- White ink transfer layline

Operating Temperature

-40°C to + 100°C
(-40°F to + 212°F)

Agency Listings

MSHA approved

Application

- Low & medium pressure hydraulic systems
- Petroleum & water-based fluids
- Construction equipment
- Agriculture equipment

Approved Fittings

- Winner 2-piece fitting (non-skive)
- TTC series

EATON

Powering Business Worldwide

Eaton
Hydraulics Group USA
14615 Lone Oak Road
Eden Prairie, MN 55344
USA
Tel: 952-937-9800
Fax: 952-294-7722
www.eaton.com/hydraulics

Eaton
Hydraulics Business Europe
Route de la Longeraie 7
1110 Morges
Switzerland
Tel: +41 (0) 21 811 4600
Fax: +41 (0) 21 811 4601

Eaton
Hydraulics Group Asia Pacific
Eaton Building
No.7 Lane 280 Linhong Road
Changning District,
Shanghai 200335
China
Tel: (+86 21) 5200 0099
Fax: (+86 21) 2230 7240